

SRW Carries a Full Line of Quality Hardscape Accessories



LG PAVER SEAL & HG PAVER SEAL

- Available in Low-Gloss or High-Gloss (Wet-Look)
- Waterbased Sealer
- Sand Stabilizer
- UV Resistant
- Environmentally Friendly
- **TRY with our new PAVER GRIP anti-slip additive**

PS PAVER SEAL

- Deep Penetrating
- Siloxane Waterbased Sealer
- Breathable
- Great for Horizontal and Vertical Applications

CLEANERS

SRW Efflorescence Cleaner and Cleaner & Degreaser

- Removes Stains and Cleans Efflorescences
- Easy Application




JOINT SET

- Available in Premix or Concentrate
- Prevents washout and increases the strength of joints while keeping ants and weeds out.



Look for SRW products at your favorite landscape supply store.

DISTRIBUTED BY:



Important notice: The recommendations and information presented herein are accurate to the best of our knowledge but will not apply to every installation. Specific applications will vary due to site conditions and installation procedures. Final determination of the use of any information or material is the sole responsibility of the user.



© SRW Products • 32020 126th Street • Princeton, MN 55371
For more information call us at 763-389-2722
Visit our website at www.srwproducts.com

Members of:



0109ADHESB

Adhesive

Retaining Wall and Paver



Professional strength adhesive for masonry, concrete, brick, block, pavers, and common landscaping materials.



Regular

VOC Compliant



For more info:
763-389-2722
www.srwproducts.com



- Ideal for wet or frozen surfaces
- Extrudes well in low temperatures
- Quick curing
- Strong, durable bond
- Water resistant
- Flexible and freeze-thaw stable

SRW Retaining Wall & Paver Adhesive has been around the block when it comes to a name that contractors ask for. It is formulated especially for masonry, concrete, brick, block, pavers and common landscaping materials. SRW Adhesives provide a fast, secure method of bonding retaining wall block, steps, corners and coping for commercial and residential walls and pavers — even on wet, frozen or damp surfaces. SRW Retaining Wall and Paver Adhesive comes in standard and VOC compliant formulas.

Directions

1. Surfaces should be clean and free from oil, grease, excessive water, ice or any other material which may deter adhesion.
2. Cut tip on slant for 1/4" or 3/8" bead. Puncture inner seal with nail or wire. Place cartridge in a caulking gun.
3. Apply adhesive with the caulking gun to only one of the surfaces to be joined. Apply in a continuous bead to ensure complete coverage. Apply no more adhesive than you can cover in 20 minutes.
4. Press surfaces together firmly. For faster curing, lift up top product and immediately reposition. Do not smear adhesive.
5. Vertical or slanted applications may require additional bracing until adhesive has dried.
6. Allow 48-hour cure time and 4-5 days before walking on any steps or heavy traffic areas.

CLEANUP

- Scrape off dried excess adhesive with a putty knife. Remove residue with mineral spirits. (Note: Test cleaning solvent on an out-of-way area to make sure it will not mar the surface to be cleaned.) **Storage life:** More than 12 months in tightly closed container at 75°F. Do not store in direct sunlight.

USER TIPS

- On tumbled products, make sure surface is clean of any dust, dirt or material that may deter proper adhesion. We recommend using a 3/8" bead.
- On grooved materials, make sure you have a full positive connection of adhesive to both surfaces.
- Best if applied at temperatures above 10°F.
- Do not use below the waterline or for continuous submersion. Not recommended for fiberglass, rubber, plastic or foam.

GUIDELINES

Application Temperatures:

0° - 120° F, for adhesives and substrates

Method of application:

Cartridge/caulking gun. Due to fast-drying characteristics, it is not practical to apply by trowel. Strong initial tack allows light pieces to be bonded with only momentary pressure.

Working time: About 30 minutes for 1/4" bead.

Coverage:

Approximate length of bead according to container size and bead diameter				
Bead Size	10.5 oz Regular	29 oz Regular	10.5 oz VOC	29 oz VOC
1/4" bead	32 ft.	89 ft.	32 ft.	89 ft.
3/8" bead	14 ft.	35 ft.	14 ft.	35 ft.

CHALKING GUNS AVAILABLE FROM SRW PRODUCTS

Economy Caulking Gun

MODEL 012

- Heavy-Duty Steel Construction
- Non-Drop
- Smooth Rod



Premium Caulking Gun

MODEL 250

- Patented Spout Cutter
- Sealer Puncture Tool
- Revolving Barrel
- 18:1 Thrust Ratio

